

## PRELIMINARY

# SCENICVIEW B22W-5

## Business Line Wide TFT display

– efficiency for the office

Issue February 2008

Pages 2

The SCENICVIEW Business Line offers best ergonomics and usability for intensive office use with a 3-in1 stand in wide format.

### Excellent visual ergonomics for the office

- 16.7 Mio. colors
- 16:10 wide format
- 1680 x 1050 maximum resolution
- 1000:1 typical Contrast
- 170° typical viewing angle

### 3-in-1 height adjustable stand

- Height adjustment
- Swivel
- Tilt

### Flexible connectivity

- Analogue D-SUB
- Digital DVI-D
- D-SUB and DVI-D cables included

### Exceptionally Eco-friendly

- TCO'03
- Energy Star
- RoHS
- WEEE

### Ready for manageability

- DisplayView™ IT Suite
- Remote inventory gathering
- Remote execution of configuration tasks



<b>Visible screen diagonal</b>	22 inch (56 cm)	
<b>Graphics display</b> (dependent on graphics processor)		
Pixels	1680 x 1050	
Pixels *)	1440 x 900	
Pixels *)	1280 x 1024	
Pixels *)	1024 x 768	
Pixels *)	800 x 600	
Pixels *)	640 x 480	
*) interpolated		
<b>Text display</b> (dependent on graphics processor)		
Pixels (max. 75 Hz)	720 x 400	
<b>Picture size</b>	474 x 296 mm	
<b>Pixel pitch</b>	0.282 mm	
<b>Frequencies</b>		
Horizontal	30 - 82 kHz	
Vertical	55 - 75 Hz	
<b>Brightness typical</b>	300 cd/m <sup>2</sup>	
<b>Contrast typical</b>	1000:1	
<b>Viewing angle typical</b>	CR>5:1	CR>10:1
Horizontal	170°	160°
Vertical	170°	160°
<b>Response time typical</b>	5 ms	
<b>Plug &amp; Play</b>	VESA DDC CI	
<b>Ease-of-use menu</b>		
Direct key access	auto adjust, brightness, mute	
Brightness / contrast	brightness, contrast, black level, auto level	
Image adjust	H, V position, clock, phase	
Audio	Volume, mute	
Color	sRGB, 6500 K, 9300 K, native, customer settings	
OSD setup	language, position, time out	
Advanced	DDCI, resolution notifier, factory recall	
Information	Model name, S/N, Resolution/mode, Signal input	
<b>Base features</b>		
Height adjust range	110 mm	
Tilt angle	-5° / + 20°	
Swivel	+/- 45°	
<b>Audio characteristics</b>		
Volume control	digital	
Audio signal input (from PC)	3.5 mm stereo phone jack	
Sound output	1.0 W (L) + 1.0 W (R)	

<b>Electrical values</b>		
Rated voltage	100 - 240 V	
Frequency	50 - 60 Hz	
Power draw typical		
Operation (w/o sound)	50 W	
Power save mode	1 W	
(Standby-, Suspend- and Off- mode)		
Soft switch off (front)	< 1 W	
Protection class	1	
<b>Temperatures / dimensions / weight</b>		
Ambient temperature (to IEC721)		
Recommended range	15°C to 32°C	
Limit	5°C to 35°C	
Dimensions (lowest position)		
(H x W x D)	402 x 511 x 212	
Dimensions without base		
(H x W x D)	343 x 511 x 58	
Weight unpacked / packed	7,6 kg / 9,8 kg	
without base unpacked	4,8 kg	
<b>Reliability typical</b>		
MTBF (demonstrated)	70,000 h	
Lifetime of LCD	50,000 h	
(brightness > 50 % of original brightness)		
<b>Compliance with standards</b>		
Product safety	EN60950	
Ergonomics	GS mark	
	ISO13406-2	
	(Pixel fault class II)	
Radiation immunity and suppression	CE certification according RFI to EC Directive 2004/108/EEC (EN55022/B, EN55024 (EN61000-3-2/-3); TCO'03	
Ecology	RoHS, WEEE, IT-Eco-declaration Energy Star (EPA 4.1)	
<b>Video input</b>	1 x D-SUB analog	
	1 x DVI-D	
<b>Data cable (1.8 m)</b>	D-SUB (15-pin) analog	
detachable on display	DVI-D digital	
<b>Power cable (1.8 m)</b>	for wall socket	
	Euro-Schuko-Type CEE7	
Integrated power supply		
Plug type on display side	IEC-320-C13	
<b>Special features</b>	Kensington Lock prepared, standardized mounting interface according VESA FPMPI (100 mm)	
<b>Order code</b>	S26361-K1258-V150	